





The Factory version's fully integrated engine echoes the lines of the swing arm and frame of the RSV 1000 R Factory.



The new concept air intake optimises engine breathing, improves performance and makes the SR look more aggressive than ever.

The more powerful, 35 Watt twin halogen headlights give maximum safety in all lighting conditions.

SO YOU KNOW ALL ABOUT SPORTS SCOOTERS. YOU'VE READ UP ON SCOOTER TECHNOLOGY AND PERFORMANCE TOO. THEN YOU KNOW YOU NEED THE NEW SR 50.

JUST TO REFRESH YOUR MEMORY, THE SR 50 WAS THE FIRST SCOOTER TO FIT 13" WHEELS, THE FIRST WITH LIQUID COOLING, THE FIRST WITH A DOUBLE DISC BRAKING SYSTEM, AND THE FIRST WITH A DIRECT INJECTION ENGINE. THE NEW SR 50 RESPONSIVE YET DEPENDABLE CARBURETTOR FUELLED TWO STROKE OR AN INNOVATIVE, SECOND GENERATION DITECH ENGINE WITH EXCEPTIONALLY SMOOTH POWER DELIVERY AND MISERLY FUEL CONSUMPTION (UP TO AN INCREDIBLE 50 KM PER LITRE!).*

AND FINISH AND EQUIPMENT ARE SUPERBIKE LEVEL. JUST LOOK AT THE MIRRORS, INTEGRATED FOOTRESTS, AND OPEN BRAKE MASTER CYLINDERS.

THE SR 50 HAS TO BE YOURS!

* ECE47 SIMULATED URBAN CYCLE.





Rear light cluster.



Practical extra storage in the nose of the seat.

Under-seat storage is big enough for a full-face helmet.



in the i, the ke do the firm a mice main feet the contains



MAYBE YOU USE YOUR SCOOTER TO GET AROUND WITH YOUR FRIENDS. IF SO, ON AN SR YOU'RE SURE TO ATTRACT THE RIGHT COMPANY! SR RIDERS ALWAYS HAVE SOMETHING IN COMMON. LIKE YOU,
THEY KNOW AGGRESSIVE STYLE,
STREAMLINED
AERODYNAMICS AND
IMPECCABLE HANDLING WHEN

EVERYBODY'S DIFFERENT, BUT ON AN SR EVERYBODY'S GOT SOMETHING TO SHARE.



IF WE WANTED TO, WE COULD WRITE A BOOK ABOUT THE **SR 50 FACTORY**'S BRAND NEW, **ACTIVE MATRIX, DIGITAL INSTRUMENT PANEL**. AFTER ALL, IT DOES HAVE AN ANALOG REV COUNTER AND A LARGE LCD DISPLAY FOR FUEL LEVEL, COOLANT TEMPERATURE, CLOCK, SPEEDOMETER, ODOMETER, DUAL TRIP COUNTERS, JOURNEY TIME, MAXIMUM SPEED, 16 STAGE TIMER, BATTERY VOLTAGE, AND COMPLETE DIAGNOSTIC SYSTEM. BUT WE SHALL LIMIT OURSELVES TO POINTING OUT THAT ALL THESE FUNCTIONS ARE ACCESSIBLE FROM CONVE-NIENT HANDLEBAR CONTROLS.

THE SR 50 R IS ALSO EQUIPPED WITH A LARGE, COMPLETE DIGITAL INSTRUMENT PANEL THAT PROVIDES READINGS FOR SPEED, CLOCK, ODOMETER AND



responsible young man!

MAYBE YOU FIT IN NEATLY WITH ONE OF THE PERSONALITIES DESCRIBED ABOVE – OR MAYBE YOU DON'T! IN ANY CASE, WE'RE SURE YOU'RE A RESPONSIBLE YOUNG MAN, AND YOUR FAMILY'S PRIDE AND JOY! SO IT'S JUST AS WELL THAT THE SR HAS WHAT IT TAKES TO KEEP EVERYBODY HAPPY, INCLUDING ADVAN-CED SAFETY SYSTEMS LIKE DOUBLE DISC BRAKING, HIGH-PERFORMANCE SHOCK ABSORBERS, AND A HOST OF HIGH-TECH COMPONENTS. IT EVEN COMES WITH A CHOICE OF TWO POWER UNITS, A TRIED AND TESTED CARBURETTOR ENGINE AND A DIRECT INJECTION ENGINE WITH THE SORT OF FUEL CONSUMPTION THAT WOULD IMPRESS EVEN SCROOGE.



SLEEK, AGGRESSIVE STYLING, TO ENSURE THAT ALL EYES TURN YOUR WAY.

A CHOICE OF ENGINES,

A RESPONSIVE CARBURETTOR DITECH ENGINE. (THE DITECH IS MILE AFTER MILE. CAPABLE OF 50 KM PER LITRE*. THAT'S SERIOUS ECONOMY!).

3. MOTORCYCLE ROAD-HOLDING, PRECISION, AGILITY

4 DOUBLE DISC BRAKES FOR BAGS OF CONTROLLABLE STOPPING POWER AND FANTASTIC BIG. JUST AS A REAL SPORTS

5 ROBUST CONSTRUCTION TO MAKE SURE THAT YOUR SR ENGINE AND A LOW-CONSUMPTION REMAINS FAITHFUL MILE AFTER

6 A DIGITAL

INSTRUMENT PANEL WITH ON-BOARD COMPUTER (FACTORY VERSION).

8. THE RIGHT SIZE. **ATTENTION TO DETAIL** TO NOT TOO SMALL, NOT TOO SATISFY EVEN THE MOST DEMANDING. SCOOTER SHOULD BE.

10. ENVIABLE EQUIPMENT, INCLUDING POWERFUL 35 WATT HEADLIGHTS, STORAGE/ COMPARTMENT IN THE SEAT NOSE, MOTORCYCLE STYLE SWITCHGEAR AND NUMBER PLATE HOLDER, AND REAR SUSPENSION WITH AN OPEN COLOURED

WHAT MORE COULD YOU WANT?

TRANSPONDER ANTI-THEFT SYSTEM. (FACTORY VERSION) AND PROVISION FOR THE BODY GUARD ARMOURED CABLE LOCK. BECAUSE YOU CAN NEVER BE TOO SURE.

^{*} ECE47 SIMULATED URBAN CYCLE.











SR 50 R FACTORY

0.1.00 11.17.01.0111			
Engine	Liquid cooled horizontal single cylinder two	Frame	Split single cradle frame in high tensile
	stroke. Electronic direct fuel injection		strength steel
Bore and stroke	40 x 39.3 mm	Front suspension	Hydraulic fork, 90 mm wheel travel
Displacement	49 cc	Rear suspension	Engine unit acting as swingarm; frame linkages
Compression ratio	11,5:1		on two radial silent block mountings; wheel
Air-oil mix aspiration	Reed valve		travel 70 mm
Fuel injection	Electronically controlled, air assisted, direct	Brakes	Front: 190 mm stainless steel disc; racing
	injection into the combustion chamber		calliper with twin opposed 32 mm pistons
Injector type	EFI low flow injector		Rear: 190 mm stainless steel disc; racing
Direct Injecton system	External opening, SMD 8 micron medium spray		calliper with twin opposed 30 mm pistons
Pressure regolator	Pressure differential maintained at 2.5 bar	Wheels	Five spoke, light alloy wheels front and rear:
Throttle body	Ø 18 mm throttle body with integtated TPS		3.50 x 13"
	(Throttle Position Sensor)	Tyres	Tubeless; front and rear 130/60 x 13"
Air compressor	Driven off crankshaft, lubricated by air-oil mix	Dimensions	Max. length 1860 mm
	in crank chamber		Max. width 705 mm
Fuel pump	6.5 – 8 bar, high pressure pump with low		Max. height 1120 mm
	electrical power absorption, < 0.5 A		Seat height 820 mm
Electronic Control Unit	8 Hz clock speed, 22 pin		Wheelbase 1290 mm
Ignition	High power inductive ignition	Tank capacity	7 litres
Starting	Electric	Colours	Speed Orange, Aprilia Black, Aprilia White,
Generator	Flywheel-magneto, 165W - 12V		Spiderman.
Lubrication	Oil injection with oil pump	Accessories	Rear luggage rack for 28 litre New Concept top box
Oil tank capacity	1,2 litres (0,2 litre reserve)		Large windshield
Gearbox	Continuous automatic converter		Sports windshield
Clutch	Automatic centrifugal dry clutch		Front footrest spoilers
Primary drive	V belt		Side stand
Final drive	Gears in oil bath		Bodyguard armoured cable lock

SR 50 R

O. 00			
Engine	Liquid cooled horizontal single cylinder two stroke.	Tyres	Tubeless; front and rear 130/60 x 13"
Bore and stroke	40 x 39.3 mm	Dimensions	Max. length 1860 mm
Displacement	49 cc		Max. width 705 mm
Compression ratio	12,1:1		Max. height 1120 mm
Air-oil mix aspiration	Reed valve		Seat height 820 mm
Carburettor	Dell'Orto PHVA 17.5		Wheelbase 1290 mm
Ignition	Capacitor Discharge Ignition (CDI)	Tank capacity	7 litres
Starting	Electric	Colours	Speed Orange, Aprilia Black, Aprilia White,
Generator	Flywheel-magneto 70W - 12V		Spiderman.
Lubrication	Separate lubrication with mechanical oil pump	Accessories	Rear luggage rack for 28 litre New Concept top box
Oil tank capacity	1,2 litres (0,2 litre reserve)		Large windshield
Gearbox	Continuous automatic converter		Sports windshield
Clutch	Automatic centrifugal dry clutch		Front footrest spoilers
Primary drive	V belt		Side stand
Final drive	Gears in oil bath		Bodyguard armoured cable lock
Frame	Split single cradle frame in high tensile		
	strength steel		
Front suspension	Hydraulic fork, 90 mm wheel travel		
Rear suspension	Engine unit acting as swingarm; frame linkages		
	on two radial silent block mountings; wheel		
	travel 70 mm		
Brakes	Front: 190 mm stainless steel disc; racing		
	calliper with twin opposed 32 mm pistons		
	Rear: 190 mm stainless steel disc; racing		
	calliper with twin opposed 30 mm pistons		
Wheels	Five spoke, light alloy wheels front and rear:		
	3.50 x 13"		

SR 50 Factory is an ecological vehicle with communitarian homologation Euro2, in the respect of the acoustic and atmospheric pollution limits.

Concessionair

Drive safely always wearing a helmet and protective clothing. Observe the laws of the road and respect the environment. Carefully read the owners' handbook. Photographs, technical data, specifications and colors shown in this brochure refer to the Italian market version and may be subject to change without prior notice. Ask your official Aprilia dealers for full details. In order to maintain your machine in a safe and efficient manner, always demand official Aprilia Spare Parts, which are guaranteed by Aprilia Quality Service in respect of current legislation.